

## Passenger Car Motor Oil (PCMO)

Combining NexLube's exceptional quality base oils with premium additives, NexLube is bringing the highest quality lubricant to the PCMO market.

The PCMO 10W-30 is a lubricant formulated for turbo-charged and natural injection gasoline engines, in the passenger car and light duty truck industries.

### Features:

- Meets or exceeds API Specification SN and ILSAC GF-5 requirements
- Lubricates and protects turbo-charged high-RPM engines
- Meets passenger car and light truck manufacturer's warranty requirements
- Protects the engine by controlling varnish, deposits, wear, and promotes cleanliness
- Conserves energy by improving fuel economy and lowers emissions
- Extends oil service intervals for all engines

### Specifications:

Specification	Test Method	10W-30 (*)
Appearance	Visual	C & B
Viscosity, cSt @ 40C	D-445	69.43
Viscosity, cSt @ 100C	D-445	10.52
Viscosity Index	D-2270	139
Flash Point, F, COC	D-92	202
Pour Point, F	D-97	-30
Color ASTM	D-1500	3
TBN, mg KOH/gr	D-974	7.6
Volatility Noack, loss % wt	D-4294	15

(\*) Expected product specifications

Consult the Material Safety Data Sheet (MSDS) for safety and handling information. To obtain the MSDS sheet, please contact NexLube.